

Portmaster Range

Duratread OTR Tires conform to the Japanese Quality Standards Bureau (JIS) and with ISO 9001:2008

Size	Ply	TRA Code	Type	inflated (mm)				50 km/h		10 km/h		Tread depth MM	Rim
				Width	Diameter	Static Loaded Radius		Load kgs	KPA	Load kgs	KPA		
12.00-20	24	E4	TT	315	1150	533		4,050	840	6,150	825	30.0	8.50
14.00-20	16	E3	TT	345	1220	552	389	3,650	375	-	-		10.00W
	20	E3	TT	345	1220	552	389	4,125	475	7,500	700	18.0	10.00W
	24	E3	TT	345	1220	552	389	4,500	550	8,500	850	18.0	10.00W
12.00-24	24	E4	TT	315	1235	586		4,050	650	6,900	825	33.0	8.50
14.00-24	16	E3	TT	375	1340	660	415	4,000	375	7,300	550	27.5	10.00W
	20	E3	TT	375	1340	660	415	4,625	475	8,500	700	27.5	10.00W
	24	E3	TT	375	1340	660	415	5,150	575	9,250	800	27.5	10.00W
	28	E3	TT	375	1340	660	415	5,600	650	10,300	975	27.5	10.00W
16.00-25	24	E3	TT/TL	440	1485	715	652	6,000	475	10,600	650	35.5	11.25/2.0
	28	E3	TL	440	1485	715	652	6,700	575	11,500	750	35.5	11.25/2.0
	32	E3	TL	440	1485	715	652	7,300	650	12,500	875	35.5	11.25/2.0
	32	E4	TL	440	1485	715	652	7,300	650	12,500	875	44.0	11.25/2.0
	36	E3	TL	440	1485	715	652	-	-	13,600	975	35.5	11.25/2.0
18.00-25	32	E3	TT/TL	498	1635	750	559	8,750	575	15,000	750	38.0	13.00/2.5
	32	E4	TT/TL	498	1635	750	559	8,750	575	15,000	750	48.0	13.00/2.5
	40	E3	TL	498	1635	750	559	9,750	575	17,000	750	38.0	13.00/2.5
	40	E4	TL	498	1635	750	559	9,750	575	17,000	750	48.0	13.00/2.5
21.00-25	28	E4	TT/TL	599	1763	805	663	9,500	425	16,500	575	54.0	15.00/3.0
	32	E4	TT/TL	599	1763	805	663	10,300	500	17,500	650	54.0	15.00/3.0
	36	E4	TT/TL	599	1763	805	663			19,000	750	54.0	15.00/3.0
	40	E4	TT/TL	599	1763	805	663			20,000	825	54.0	15.00/3.0
21.00-35	28	E4	TL	610	2037	945	660	11,200	425	19,500	575	56.0	15.00/3.0
	32	E4	TL	610	2037	945	660	12,150	500	21,200	650	56.0	15.00/3.0
	36	E4	TL	610	2037	945	660	12,850	550	23,000	750	56.0	15.00/3.0
	40	E4	TL	610	2037	945	660	14,000	600			56.0	15.00/3.0
24.00-35	48	E4	TL	653	2127	970	720	18,500	650	31,500	850	58.0	17.00/3.5

Technical data relates to DURATread branded tires only