

Dear Sir  
I am deal with TRIANLGE brand High quality OTR, please see below update catalog.



Size	Type	Ind Code	Rim Width & Flange	Min Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY		
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3	
13.00R25	TL569	E-3	10.00/1.5		13.8 350	51.2 1300			31.5 25			
14.00R24	TB536 * / ** / ***	E-2	10.00W	17.7 450	14.8 375	53.9 1368	24.7 627	31.5 25	110	140	170	
		G-2	10.00VA		14.8 375	53.9 1368	24.4 619	31.5 25				
		L-2	10.00VA		14.8 375	53.9 1368		31.5 25				
	TB586 ***	E-2	10.00W	17.7 450	14.8 375	53.9 1368	24.7 627	27.7 22	125	160	195	
TB516S * / ** / ***	E-4	10.00W	17.7 450	14.8 375	55.8 1418	24.7 627	45.4 36	85	105	130		
14.00-24	TL612 18,20,24,28PR	E-3	10.00	17.7 450	14.8 375	53.9 1370	25.5 647	37.8 30				
	TL558 24PR	E-3	10.00	17.7 450	14.8 375	53.9 1370	25.5 648	37.8 30				
14.00-24TG	TL508 12PR	E-2	8.00TG		14.2 360	53.1 1350	24.0 611	31.5 25				



Size	Type	Ind Code	Rim Width & Flange	Min Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY		
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3	
14.00R25	TB526 ***	E-3	10.00/2.0	17.7 450	14.8 375	53.9 1368	24.4 621	32.8 26	85	105	130	
	TB536 * / ** / ***	E-2	10.00/1.5	17.7 450	14.8 375	53.9 1368		31.5 25	110	140	170	
	TB586 ***	E-2	10.00/1.5	17.7 450	14.8 375	53.9 1368	24.6 626	27.7 22	125	160	195	
	TB516S * / ** / ***	E-4	10.00/1.5	17.7 450	14.8 375	55.8 1418		45.4 36	85	105	130	
14.00-25	TL558 28PR	E-3	10.00/2.0	17.7 450	14.8 375	53.9 1370	25.5 648	37.8 30				
16.00R25	TB586 ***	E-2	11.25/2.0	24.0 518	17 432	58.8 1493	26.9 682	30.2 24	165	210	255	
	TL558S * / ** / ***	E-4	11.25/2.0	24.0 518	17 432	61.0 1548		64.3 51				
	TSMS * / ** / ***	L-4S	11.25/2.0	24.0 518	17 432	61.0 1548	26.0 661	64.3 51				
16.00-25	TL612 28PR	TL612	11.25/2.0	20.2 513	16.9 430	58.9 1495	27.7 705	37.8 30				





TB516S



TL558S



TB589



TSMS+



L-5S



TL510



TL612

Size	Type	Ind Code	Rim Width & Flange	Min Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY						
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3					
18.00R25	TB589 ***	E-2	13.00/2.5	23.5	598	19.6	498	63.68	1617	28.9	734	32.8	26	200	240	300
	TB516S ** / ***	E-4	13.00/2.5	23.5	598	19.6	498	65.9	1673	28.9	734	56.7	45	150	190	240
	TL558S ** / ***	E-4	13.00/2.5	23.5	598	19.6	498	65.9	1673			68.0	54			
	TSMS+ **	L-5S	13.00/2.5	23.5	598	19.6	498	65.9	1673	28.0	710	100.8	80			
18.00-25	L-5S 40PR	L-5S	13.00/2.5	23.1	587	19.7	500	63.6	1615	29.9	759	68.0	54			
	TL510 28.32.40PR	E-4	13.00/2.5	23.1	587	19.7	500	63.6	1615	29.9	759	98.9	78.5			
	TL612 28.32.40PR	E-3	13.00/2.5	23.1	587	19.7	500	63.6	1615	29.9	759	40.3	32			



TB526S



TL510



TR139

Size	Type	Ind Code	Rim Width & Flange	Min Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY						
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3					
18.00R33	TB526S **	E-4	13.00/2.5	23.1	587	19.6	498	73.9	1877	33.1	841	64.0	51	160	190	270
18.00-33	TL510 32PR	E-4	13.00/2.5	23.1	587	19.7	500	71.7	1820	33.9	861	69.3	55			
21.00-25	TR139 16PR	E-1	15.00/3.0			22.4	570	66.3	1685	29.4	748	17.6	14			
21.00R33	TB526S **	E-4	15.00/3.0	27.6	701	22.5	571	78.8	2001	36.0	914	66.0	52	190	230	300





TB526S



TL558



TL510

Size	Type	Ind Code	Rim Width & Flange	Min Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS	Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY		
					Overall Width in mm	Overall Diameter in mm			Static Load Rad in mm	T1	T2
21.00R35	TB526S **	E-4	15.00/3.0	27.6 701	22.5 572	80.8 2052		76.0 80	230	280	365
21.00-35	TL558 32PR	E-3	15.00/3.0	27.6 701	22.4 570	78.9 2005	34.7 947	56.7 45			
24.00R35	TB526S **	E-4	17.00/3.5	31.3 795	25.7 653	85.6 2175		82.0 65	280	350	460
24.00-35	TL510 42PR	E-3	17.00/3.5	31.3 795	25.8 655	83.7 2125	39.4 1001	56.7 45			



TB526S



TL588



TB599

Size	Type	Ind Code	Rim Width & Flange	Min Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS	Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY				
					Overall Width in mm	Overall Diameter in mm			Static Load Rad in mm	T1	T2A	T2B	T2C
27.00R49 **	TB526S	E-4	19.50/4.0		27.6 700	105.8 2688		96 76	315	345	435	480	560
33.00R51 **	TL588	E-4	24.00/5.0		34.6 879	118.8 3018		107 85	350	415	520	575	695
36.00R51 **	TB599	E-4	26.00/5.0		40.1 1019	128.0 3251		129 102	485	655	820	905	975
37.00R57 **	TB599	E-4	27.00/6.0		41.5 1054	135.5 3442		129 102	550	685	860	950	1075
40.00R57 **	TB599	E-4	29.00/6.0		43.8 1111	140.5 3569		129 102	600	840	1050	1155	1190
46/90R57 **	TB599	E-4	32.00/6.0		46.8 1187	140.5 3569		129 102	625	875	1095	1204.5	1300





TB515



TB516



TL508



TL812

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
15.5-25	TL612 12PR	E-3	12.00/1.3		15.6	395	50.2	1275	22.8	580	31.5	25			
	TL508 12PR	E-2	12.00/1.3		15.6	395	50.2	1275	22.8	580	31.5	25			
17.5R25	TB515 * / **	G-2	14.00/1.5		17.5	445	53.1	1348	24.0	610	34.0	27			
		L-2	14.00/1.5		17.5	445	53.1	1348	23.6	600	34.0	27			
	TB516 * / **	E-3	14.00/1.5		17.5	445	53.1	1348	23.6	600	32.8	26	110	140	170
		L-3	14.00/1.5		17.5	445	53.1	1348	23.6	600	32.8	26			
17.5-25	TL612 12,16PR	E-3	14.00/1.5		17.5	445	53.1	1350	24.0	611	32.1	25.5			
	TL508 12,16PR	E-2	14.00/1.5		17.5	445	53.1	1350	24.0	611	31.5	25			



TB515



TB516



TL538S+



TL508



TL812

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
20.5R25	TB515 * / **	G-2	17.00/2.0		20.5	521	58.8	1493	26.3	669	37.8	30			
		L-2	17.00/2.0		20.5	521	58.8	1493	25.8	656	37.8	30			
	TB516 * / **	E-3	17.00/2.0		20.5	521	58.8	1493	25.8	656	37.8	30	120	150	190
		L-3	17.00/2.0		20.5	521	58.8	1493	25.8	656	37.8	30			
	TL538S+ * / **	L-5	17.00/2.0		20.5	521	60.9	1548	25.8	656	88.2	70			
20.5-25	TL612 16,20PR	E-3	17.00/2.0		20.5	520	58.7	1490	26.3	668	35.9	28.5			
		E-3	17.00/2.0		20.5	520	58.7	1490	26.3	668	36.5	29			
	TL508 12,16PR	E-2	17.00/2.0		20.5	520	58.7	1490	26.3	668	35.9	28.5			





TM518 TL528 TL559S+ TL538S+ TB516 / TB516-II TB598S TL508 TL612

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
23.5R25	TM518 */**	E-2	19.50/2.5		23.2	590	64.8	1647	28.3	720	37.8	30	170	200	260
		L-2	19.50/2.5		23.2	590	64.8	1647	27.8	705	37.8	30			
	TB516 */**	E-3	19.50/2.5		23.6	600	64.8	1647	28.5	724	40.3	32	145	170	230
		L-3	19.50/2.5		23.6	600	64.8	1647	27.8	706	40.3	32			
	TB516-II *	L-3	19.50/2.5		24.0	609	63.4	1611	28.5	714	40.3	32			
	TL528 */**	E-3	19.50/2.5		23.8	605	64.8	1647	28.7	730	50.4	40	150	190	230
		L-3	19.50/2.5		23.8	605	64.8	1647	28.7	730	50.4	40			
	TB598S **	E-4	19.50/2.5		23.8	605	64.2	1630	28.3	720	59.2	47	115	135	185
TL538S+ */**	L-5	19.50/2.5		23.8	605	65.2	1657	27.8	705	97.0	77				
TL559S+ **	L-5	19.50/2.5		23.8	605	65.2	1657	27.8	705	103.3	82				
23.5-25	TL612 16,18,20PR	E-3	19.50/2.5		23.4	595	63.6	1615	28.3	719	39.7	31.5			
		E-3	19.50/2.5		23.4	595	63.6	1615	28.3	719	39.7	31.5			
	TL508 16PR	E-2	19.50/2.5		23.4	595	63.6	1615	28.3	719	39.7	31.5			



TB516 TL538S+ TL559S+ TB598S TL612

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
29.5R25	TB516 */**	E-3	25.00/3.0		29.8	756	73.8	1874	32.6	829	47.9	38	180	230	290
		L-3	25.00/3.0		29.8	756	73.8	1874	31.8	807	47.9	38			
	TB598S **	E-4	25.00/3.0		30.1	764	73.5	1867	33.7	856	70.6	56	135	175	225
	TL538S+ */**	L-5	25.00/3.0		29.3	743	75.0	1906	31.8	807	118.4	94			
	TL559S+ **	L-5	25.00/3.0		29.7	754	74.9	1902	31.8	807	124.7	99			
29.5-25	TL612 22,26PR	E-3	25.00/3.5		29.5	750	73.8	1875	32.5	826	54.2	43			





Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
26.5R25	TB516 * / **	E-3	22.00/3.0		26.5	673	68.9	1750	30.5	775	44.0	35	155	190	240
		L-3	22.00/3.0		26.5	673	68.9	1750	29.8	758	44.0	35			
	TL559 ***	IND-3	22.00/3.0		26.5	673	68.9	1750			44.0	35			
	TB598S **	E-4	22.00/3.0		26.5	673	70.8	1798	30.5	775	68.0	54	125	150	195
	TL538S+ * / **	L-5	22.00/3.0		26.5	673	70.8	1798	29.4	748	108	86			
	TL559S+ **	L-5	22.00/3.0		26.5	673	70.8	1798	29.8	758	113	90			
	TSMS+ * / **	L-5S	22.00/3.0		26.5	673	70.8	1798	29.8	758	118	94			
26.5-25	L-5S 36PR	L-5S	22.00/3.0		26.5	675	70.9	1800	31.3	795	109.6	87			
		TL612 29.2PR	E-4	22.00/3.0		26.5	675	70.9	1800	31.3	795	68.0	54		
		E-3	22.00/3.0		26.5	675	70.9	1800	31.3	795	44.1	35			



Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
29.5R29	TB516 * / **	E-3	25.00/3.0		29.8	757	78.1	1983	34.5	876	47.9	38	200	250	330
		L-3	25.00/3.0		29.8	757	78.1	1983			47.9	38			
29.5-29	TL612 43PR	E-3	25.00/3.5		29.5	750	77.8	1975	34.1	867	54.2	43			
33.25R29	TL568+ * / **	E-3	27.00/3.5		33.25	845	82.3	2090			55.0	44	310	390	490





TL535S+



TB598



TL520

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
35/65R33	TL535S+ */**	L-5	28.00/3.5		35.0	889	81.78	2077		119.7	95				
35/65-33	TL520 42PR	L-5	28.00/3.5		35.0	890	81.7	2075	35.7	908	122.2	97			
45/65-45	TL520 46.58PR	L-5	36.00/4.5		44.9	1140	107.7	2735	46.4	1179	146.1	116			
750/65R25	TB598 */**	E-3	24.00/3.0		29.4	746	63	1600		52.9	42	130	190	250	
		L-3	24.00/3.0		29.4	746	63	1600		52.9	42				
775/65R29	TB598 */**	E-3	24.00/3.5		30.4	771	68.7	1745		55.4	44	195	235	325	
		L-3	24.00/3.5		30.4	771	68.7	1745		55.4	44				
875/65R29	TB598 */**	E-3	28.00/3.5		34.2	868	73.5	1868	32.5	825	63.0	50	230	285	360
		L-3	28.00/3.5							63.0	50				



TL566



TL506

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY					
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3				
460/85R30	TL566	E-2	W14L		17.9	455	178.9	4544	75.6	1920	61.7	49			
1500x600-635	TL506 14PR	E-2	19.50/2.5		23.6	600	59.1	1500	26.5	672	31.5	25			





L-4S

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY		
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3	
12.00-24	L-4S 20PR	L-4S	8.5	15.4 391	12.4 315	50.2 1275	23.8 604	42.2 33.5				



TB812



TB822

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS		Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY		
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm	T1		T2	T3	
23.1-26	TB822 12,14PR	E-7	DW20		23.1 587	62.2 1581	27.8 705	35.3 28				
	TB812	R-3	DW20		23.4 595	59.1 1500	26.5 672	18.9 15				







TB812



TR139



TR128

Size	Type	Ind Code	Rim Width & Flange	Min. Dual Spacing in mm	INFLATED DIMENSIONS		LOADED DIMENSIONS	Tread Depth 32 <sup>nd</sup> in mm	PERFORMANCE CAPABILITY		
					Overall Width in mm	Overall Diameter in mm	Static Load Rad in mm		T1	T2	T3
24-21	TB812 14PR	R-3	18.0/1.5		24.0 610	53.9 1370	24.4 619	22.7 18			
27.25-21	TR139 16PR	E-1	19.50/1.5		27.0 685	59.4 1510	26.6 676	20.6 16			
66x44.00-25	TR128 6,16,20PR	E-7	36.0TH		44.0 1118	67.0 1702	29.7 755	12.6 10			

