

E3/L3 Rock Load 380 Technical Data

For Loading and Earthmoving machines

Dimension	Ply rating	TRA Code	TT or TL	mm	mm	mm	At 50 Km/h		At 10 Km/h		mm	Compound Type
				Overall Width	Overall Diameter	Static loaded radius	Load (kgs)	Air (KPA)	Load (kgs)	Air (KPA)	Tread depth	
17.5-25	16 PR	L3	TL	457.0	1359.0	597.0			7,300	475	26.0	Cut
	20 PR	L3	TL	457.0	1359.0	597.0			8,250	575	26.0	Cut
20.5-25	16 PR	E3/L3	TL	540.0	1470.0	665.0	5,450	275	8,250	350	30.0	Cut
	20 PR	E3/L3	TL	540.0	1470.0	665.0	6,000	325	9,500	450	30.0	Cut
23.5-25	16 PR	E3/L3	TL	622.0	1620.0	729.0	6,150	225	9,500	300	35.0	Cut
	20 PR	E3/L3	TL	622.0	1620.0	729.0	7,300	300	10,900	375	35.0	Cut
	24 PR	E3/L3	TL	622.0	1620.0	729.0	8,000	350	12,500	475	35.0	Cut
	28 PR	L3	TL	622.0	1620.0	729.0			13,600	550	35.0	Cut
	32 PR	L3	TL	622.0	1620.0	729.0			14,500	625	35.0	Cut
26.5-25	20 PR	E3/L3	TL	691.0	1750.0	759.0	8,250	250	13,200	350	35.0	Cut
	24 PR	E3/L3	TL	691.0	1750.0	759.0	9,250	300	14,000	400	35.0	Cut
	28 PR	E3/L3	TL	691.0	1750.0	759.0	10,000	350	15,500	475	35.0	Cut

E3/L3 Rock Load 590 Technical Data

For Loading and Earthmoving machines

Dimension	Ply rating	TRA Code	TT or TL	mm	mm	mm	At 50 Km/h		At 10 Km/h		mm	Compound Type
				Overall Width	Overall Diameter	Static loaded radius	Load (kgs)	Air (KPA)	Load (kgs)	Air (KPA)	Tread depth	
29.5-25	22 PR	E3/L3	TL	798.0	1892.0	851.0	10,000	250	15,000	325	40.0	Cut
	28 PR	E3/L3	TL	798.0	1892.0	851.0	11,500	325	17,500	425	40.0	Cut
	34 PR	E3/L3	TL	798.0	1892.0	851.0	13,200	400	20,000	525	40.0	Cut

RL 380



RL 590